



HORIZONTAL DRILLING HEAD 3-SPINDLE DRILLING UNIT

www.metalservice.pl

technical data

-	3 spindles	32 mm pitch*
	Drive 1:1.6	4400 RPM at 2600 RPM drive
	Drilling stroke	100 mm
•	Easy installation	Weeke standard
•	Aluminum body P 7075	Lightweight and durability
Hardened, ground spindles and gears		Longevity and precision

HEAD FEATURES

We are an experienced manufacturer of horizontal drilling heads designed for precise side drilling. We offer heads with different numbers of spindles and customizable spacing according to individual needs.

HEAD ADAPTED TO YOUR NEEDS – WE WILL ADJUST THE DRILL SPACING AND PARAMETERS

TO ANY TYPE OF MACHINING.

Features

Highest quality bearings: SKF, NTN, EZO

Unmatched precision – perfect spindle synchronization High durability – solid, hardened components Work efficiency – 3 drillings in one cycle* Easy integration – standard Weeke** mounting

* Number of spindles from 1 to 12, spindle spacing from 16mm

Available standard mountings for BIESSE, IMA, and others.



LET'S STAY IN TOUCH

METAL SERVICE Sp. z o.o. DZIARNÓWKO 6A,14-200 IŁAWA

WOJ. WARMIŃSKO-MAZURSKIE



+48 693 076 801









